



Fixed Coaxial Attenuator

WA38

DC - 6.0 GHz

300 WATTS



Standard Nominal Values and Deviations:

Attenuation (dB)	Accuracy \pm dB
	WA38
10 - 30	1.5
40	1.75

Maximum VSWR:

Frequency (GHz)	VSWR
	WA38
DC - 6.0	1.25

Features

Type N, DIN 7/16 or 4.3-10 stainless steel Male/Female connectors per MIL-STD-348A. Type N connector interface dimensions mate non-destructively with MIL-PRF-39012. DIN 7/16 connector conforms to DIN 47223, IEC 169-4, VG 95250, CECC 22190. 4.3-10 connectors mate non-destructively with DIN EN 61169-54 and IEC 61169-54 interfaces. Designed to meet MIL-DTL-3933 environmental specification.

Specifications

Nominal Impedance: 50 ohms.

Frequency Range: DC - 6.0 GHz

Nominal dB Values: 10 - 40 dB

Power Coefficient: < 0.005 dB/dB/W;
Unidirectional in power.

Power Rating: 300 W average to 25°C ambient temperature, de-rated linearly to 30 watts at 125° C, 10 KW peak (5µsec pulse width, 1.5% duty cycle).

Temperature Range: -55°C to +125°C.

Temperature Coefficient: < 0.0004 dB/dB/°C.

Construction: Black aluminum alloy body with passivated stainless steel connectors. Gold plated beryllium copper or stainless steel contacts. RoHS compliant.

Dimensions:

Connector Type (- code)	Length
	Dimension 'A'
N-Type F -03	14.9 (.59)
N-Type M -04	22.7 (.89)
DIN 7/16 F -07	30.5 (1.2)
DIN 7/16 M -08	31.8 (1.25)

Weight: 1.3 (45.9)

Height: 51.8 (2.04)

Width: 79.2 (3.12)

Note: Dimensions are given in mm (in), or kg (oz). Weight figure is nominal, with our standard connector configuration. Additional connector options may be available.

Calibration: Insertion Loss and VSWR performed across frequency range. Calibration test data available at additional cost.

Low Intermodulation Option: Add -LIM after connector option to specify low intermodulation.