




Termination

WA1423B

DC – 4.0 GHz

50 WATTS



Features

Type N, TNC, or SMA stainless steel M/F connector per MIL-STD-348A, interface dimensions mate nondestructively with MIL-PRF-39012. Designed to meet MIL-DTL-3933 environmental specification. Unit may be mounted in any position.

Specifications

Nominal Impedance: 50 ohms.

Frequency Range: DC - 4.0 GHz.

Power Rating: 50 W maximum average rated power to 25°C ambient temperature, de-rated linearly to 2.5 W at 125°C. 5 kW peak power (5 µsec pulse width, 0.5% duty cycle).

Temperature Range: -55°C to +125°C.

Construction: Black aluminum alloy body with passivated stainless steel connectors. Gold plated beryllium copper or stainless steel contacts. RoHS Compliant.

Calibration: VSWR performed across frequency range. Calibration test data available at additional cost.

Maximum VSWR:

Frequency (GHz)	VSWR
	WA1423B
DC - 4.0	1.2

Dimensions:

Connector Type (- code)	Length
	Dimension 'A'
SMA F -01	9.8 (.39)
SMA M -02	10.9 (.43)
N-Type F -03	14.9 (.59)
N-Type M -04	22.7 (.89)
TNC F -05	14.4 (.57)
TNC M -06	17.7 (.70)

Weight: 0.28 (9.88)
Height: 37.08 (1.46)
Width: 38.1 (1.5)
Mounting: 6x 6-32, 0.3"

Note: Dimensions are given in mm (in), or kg (oz). Weight figure is nominal, with our standard connector configuration. Additional connector options may be available.

Low Intermodulation Option: Add -LIM after connector option to specify low intermodulation attribute.