


Termination

WA1452

DC – 4.0 GHz

25 WATTS



Features

Type N, DIN 7/16, TNC or SMA stainless steel M/F connector per MIL-STD-348A, interface dimensions mate nondestructively with MIL-PRF-39012. Designed to meet MIL-DTL-3933 environmental specification. Unit may be mounted in any position.

Maximum VSWR:

Frequency (GHz)	VSWR WA1452
DC - 2.0	1.1
2.0 - 4.0	1.2

Specifications

Nominal Impedance: 50 ohms.

Frequency Range: DC - 4.0 GHz.

Power Rating: 25 W maximum average rated power to 25°C ambient temperature, de-rated linearly to 1.5 W at 125°C. 5 kW peak power (5 µsec pulse width, 0.25% duty cycle).

Temperature Range: -55°C to +125°C.

Construction: Black aluminum alloy body with passivated stainless steel connector. Gold plated beryllium copper or stainless steel contacts. RoHS Compliant.

Calibration: VSWR performed across frequency range. Calibration test data available at additional cost.

Low Intermodulation Option: Add -LIM after connector option to specify low intermodulation.

Dimensions:

Connector Type (- code)	Length
	Dimension 'A'
SMA F -01	9.8 (.39)
SMA M -02	10.9 (.43)
N-Type F -03	14.9 (.59)
N-Type M -04	22.7 (.89)
TNC F -05	14.4 (.57)
TNC M -06	17.7 (.70)
7/16 DIN F -07	30.5 (1.2)
7/16 DIN M -08	31.8 (1.25)

Weight: .28 (9.88)
Diameter: 38.1 (1.5)

Note: Dimensions are given in mm (in), or kg (oz). Weight figure is nominal, with our standard connector configuration. Additional connector options may be available.